


Perskoppelingen HP serie

BSP Buitendraad




oa

BSP Buitendraad

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	S			bar
HP-12BM12	19	12	3/4"	3/4"-14	35	97	32			420
HP-16BM16	25	16	1"	1"-11	41	114	41			414
HP-20BM16	25	16	1"	1 1/4"-11	44	117	50			414
HP-20BM20	31	20	1 1/4"	1 1/4"-11	46	134	50			414
HP-24BM24	38	24	1 1/2"	1 1/2"-11	49	143	55			345
HP-32BM32	51	32	2"	2"-11	56	154	70			345

BSPT Buitendraad



oa

oa

oa

oa

oa

BSPT Buitendraad


GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	S			bar
HP-12BMT12	19	12	3/4"	3/4"-14	34	96	27			420
HP-16BMT16	25	16	1"	1"-11	40	113	36			414
HP-20BMT20	31	20	1 1/4"	1 1/4"-11	47	135	46			414
HP-24BMT24	38	24	1 1/2"	1 1/2"-11	48	142	50			345
HP-32BMT32	51	32	2"	2"-11	57	155	65			345

Perskoppelingen HP serie

3

BSP Wartel

BSP Wartel




oa

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	S	O'Ring	bar	
HP-12WMBF12	19	12	3/4"	3/4"-14	25	87	32	16x1,5	420	
HP-16WMBF16	25	16	1"	1"-11	30	103	41	22x1,5	414	
HP-20WMBF16	25	16	1"	1 1/4"-11	33	106	50	28,3x1,78	414	
HP-20WMBF20	31	20	1 1/4"	1 1/4"-11	35	122	50	28,3x1,78	414	
HP-24WMBF24	38	24	1 1/2"	1 1/2"-11	36	130	60	33,05x1,78	345	
HP-32WMBF32	51	32	2"	2"-11	40	138	75	44,17x1,78	345	

BSP Wartel 90"

BSP Wartel 90"




oa

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	K	S	O'Ring	bar
HPS-12WMBF90S-12	19	12	3/4"	3/4"-14	55	117	63	32	16x1,5	420
HPS-16WMBF90S-16	25	16	1"	1"-11	71	144	79	41	22x1,5	414
HPS-20WMBF90S-16	25	16	1"	1 1/4"-11	71	144	81	50	28,3x1,78	414
HPS-20WMBF90S-20	31	20	1 1/4"	1 1/4"-11	90	177	96	50	28,3x1,78	414
HPS-24WMBF90S-24	38	24	1 1/2"	1 1/2"-11	107	201	113	60	33,05x1,78	345
HPS-32WMBF90S-32	51	32	2"	2"-11	142	240	140	75	44,17x1,78	345

BSP Wartel 45"

BSP Wartel 45"




oa

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	K	S	O'Ring	bar
HPS-12WMBF45S-12	19	12	3/4"	3/4"-14	68	130	32	32	16x1,5	420
HPS-16WMBF45S-16	25	16	1"	1"-11	86	159	39	41	22x1,5	414
HPS-20WMBF45S-16	25	16	1"	1 1/4"-11	88	161	41	50	28,3x1,78	414
HPS-20WMBF45S-20	31	20	1 1/4"	1 1/4"-11	107	195	47	50	28,3x1,78	414
HPS-24WMBF45S-24	38	24	1 1/2"	1 1/2"-11	126	220	55	60	33,05x1,78	345
HPS-32WMBF45S-32	51	32	2"	2"-11	160	258	66	75	44,17x1,78	345

Perskoppelingen HP serie

JIC buitendraad


JIC buitendraad



GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	S			bar
HP-17JMM12	19	12	3/4"	1 1/16"-12	38	99	27			420
HP-19JMM12	19	12	3/4"	1 3/16"-12	39	101	32			420
HP-21JMM12	19	12	3/4"	1 5/16"-12	41	102	36			420
HP-21JMM16	25	16	1"	1 5/16"-12	42	114	36			414
HP-26JMM16	25	16	1"	1 5/8"-12	45	117	46			414
HP-26JMM20	31	20	1 1/4"	1 5/8"-12	47	134	46			414
HP-30JMM20	31	20	1 1/4"	1 7/8"-12	51	139	50			414
HP-30JMM24	38	24	1 1/2"	1 7/8"-12	52	145	50			345
HP-40JMM32	51	32	2"	2 1/2"-12	63	160	65			345

NPT buitendraad

NPT buitendraad




GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	S			bar
HP12MNM12	20	12	3/4"	3/4"-14	34	98	27			420
HP16MNM12	20	12	3/4"	1"-11,5	42	103	36			420
HP16MNM16	25	16	1"	1"-11,5	42	115	36			420
HP20MNM16	25	16	1"	1 1/4"-11,5	45	118	46			420
HP20MNM20	32	20	1 1/4"	1 1/4"-11,5	47	135	46			420
HP24MNM20	32	20	1 1/4"	1 1/2"-11,5	50	137	50			420
HP24MNM24	40	24	1 1/2"	1 1/2"-11,5	50	144	50			345
HP32MNM32	50	32	2"	2"-11,5	55	153	60			345

Perskoppelingen HP serie

JIC Wartel

JIC Wartel




oa

oa

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L		S		bar
HP-17WJFM12	19	12	3/4"	1 1/16"-12	20	82		32		420
HP-19WJFM12	19	12	3/4"	1 3/16"-12	21,5	83		36		420
HP-21WJFM12	19	12	3/4"	1 5/16"-12	22,5	84		41		420
HP-21WJFM16	25	16	1"	1 5/16"-12	23,5	96		41		414
HP-26WJFM16	25	16	1"	1 5/8"-12	28	101		50		414
HP-26WJFM20	31	20	1 1/4"	1 5/8"-12	29	117		50		414
HP-40WJFM20	31	20	1 1/4"	1 7/8"-12	29,5	117		60		345
HP-30WJFM24	38	24	1 1/2"	1 7/8"-12	30	124		60		345
HP-40WJFM32	51	32	2"	2 1/2"-12	37	135		75		345

JIC Wartel 90"

JIC Wartel 90"



oa


oa

oa

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	K	S		bar
HPS-17JF90S-12	19	12	3/4"	1 1/16"-12	55	117	58	32		420
HPS-19JF90S-12	19	12	3/4"	1 3/16"-12	55	117	59	36		420
HPS-21JF90S-12	19	12	3/4"	1 5/16"-12	55	117	63	41		420
HPS-21JF90S-16	25	16	1"	1 5/16"-12	71	144	73	41		414
HPS-26JF90S-16	25	16	1"	1 5/8"-12	71	144	76	50		414
HPS-26JF90S-20	31	20	1 1/4"	1 5/8"-12	90	177	91	50		414
HPS-30JF90S-20	31	20	1 1/4"	1 7/8"-12	90	177	91	60		414
HPS-30JF90S-24	38	24	1 1/2"	1 7/8"-12	107	201	106	60		345
HPS-40JF90S-32	51	32	2"	2 1/2"-12	140	240	139	75		345

JIC Wartel 45"

JIC Wartel 45"



oa


oa

oa

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	K	S		bar
HPS-17JF45S-12	19	12	3/4"	1 1/16"-12	64	126	28	32		420
HPS-19JF45S-12	19	12	3/4"	1 3/16"-12	65	127	29	36		420
HPS-21JF45S-12	19	12	3/4"	1 5/16"-12	68	130	32	41		420
HPS-21JF45S-16	25	16	1"	1 5/16"-12	82	155	35	41		414
HPS-26JF45S-16	25	16	1"	1 5/8"-12	84	157	37	50		414
HPS-26JF45S-20	31	20	1 1/4"	1 5/8"-12	103	191	43	50		414
HPS-30JF45S-20	31	20	1 1/4"	1 7/8"-12	103	191	43	60		414
HPS-30JF45S-24	38	24	1 1/2"	1 7/8"-12	121	215	50	60		345
HPS-40JF45S-32	51	32	2"	2 1/2"-12	158	256	65	75		345

Perskoppelingen HP serie


ORFS Buitendraad



ORFS Buitendraad

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L		S	O'Ring**	bar
HP-12ORM12 oa	19	12	3/4"	1 3/16"-12	34	95		32	18,77x1,78	420
HP-16ORM16 oa	25	16	1"	1 7/16"-12	37	110		41	23,52x1,78	414
HP-20ORM20 oa	31	20	1 1/4"	1 11/16"-12	40	128		46	29,87x1,78	250
HP-24ORM24 oa	38	24	1 1/2"	2"-12	43	136		55	37,82x1,78	250


ORFS Wartel



ORFS Wartel

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L		S		bar
HP-12LORF12	19	12	3/4"	1 3/16"-12	35	97		36		420
HP-16LORF16	25	16	1"	1 7/16"-12	37	110		41		414
HP-20LORF20	31	20	1 1/4"	1 11/16"-12	38	126		50		250
HP-24LORF24	38	24	1 1/2"	2"-12	39	132		60		250


ORFS Wartel 90"



ORFS Wartel 90"

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	K	S		bar
HPS-12LORF90S-12	19	12	3/4"	1 3/16"-12	56	118	55	36		420
HPS-16LORF90S-16	25	16	1"	1 7/16"-12	71	144	67	41		414
HPS-20LORF90S-20	31	20	1 1/4"	1 11/16"-12	90	177	81	50		250
HPS-24LORF90S-24	38	24	1 1/2"	2"-12	107	201	95	60		250

ORFS Wartel 45"



ORFS Wartel 45"


GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	K	S		bar
HPS-12LORF45S-12	19	12	3/4"	1 3/16"-12	63	125	26	36		420
HPS-16LORF45S-16	25	16	1"	1 7/16"-12	78	151	31	41		414
HPS-20LORF45S-20	31	20	1 1/4"	1 11/16"-12	96	184	36	50		250
HPS-24LORF45S-24	38	24	1 1/2"	2"-12	113	207	42	60		250

** Buitendraad wordt geleverd zonder o-ring !

Perskoppelingen HP serie

Pijpopcode


Metrische pijpopcode zware serie



GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	S	E (PIPE)	bar	
oa HP-30ME20-12	19	12	3/4"	M 30x2	31	93		30	20	420
HP-36ME25-12	19	12	3/4"	M 36x2	35	97		36	25	420
oa HP-36ME25-16	25	16	1"	M 36x2	36	109		36	25	414
HP-42ME30-16	25	16	1"	M 42x2	40	113		46	30	280
oa HP-42ME30-20	31	20	1 1/4"	M 42x2	42	130		46	30	250
HP-52ME38-20	31	20	1 1/4"	M 52x2	46	134		55	38	250
HP-52ME38-24	38	24	1 1/2"	M 52x2	47	141		55	38	250

Metrische wartel


Metrische wartel 24° conus zware serie



GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	S	O'Ring	bar	
oa HP-30MSOF20-12	19	12	3/4"	M 30x2	33	95		36	16,3x2,4	420
HP-36MSOF25-12	19	12	3/4"	M 36x2	36	98		41	20,3x2,4	420
HP-36MSOF25-16	25	16	1"	M 36x2	37	110		41	22x2	414
HP-42MSOF30-16	25	16	1"	M 42x2	39	112		50	25,3x2,4	280
oa HP-42MSOF30-20	31	20	1 1/4"	M 42x2	41	128		50	25,3x2,4	250
HP-52MSOF38-20	31	20	1 1/4"	M 52x2	43	131		60	33,3x2,4	250
HP-52MSOF38-24	38	24	1 1/2"	M 52x2	44	138		60	33,3x2,4	250

Metrische wartel


Metrische wartel 24° conus zware serie 90°



GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	K	S	O'Ring	bar
oa HPS-30MSOF20-90S-12	19	12	3/4"	M 30x2	55	117	60	36	16,3x2,4	420
HPS-36MSOF25-90S-12	19	12	3/4"	M 36x2	55	117	60	41	20,3x2,4	420
HPS-36MSOF25-90S-16	25	16	1"	M 36x2	71	144	71	41	22x2	414
HPS-42MSOF30-90S-16	25	16	1"	M 42x2	71	144	71	50	25,3x2,4	280
oa HPS-42MSOF30-90S-20	31	20	1 1/4"	M 42x2	90	177	85	50	25,3x2,4	250
HPS-52MSOF38-90S-20	31	20	1 1/4"	M 52x2	90	177	86	60	33,3x2,4	250
oa HPS-52MSOF38-90S-24	38	24	1 1/2"	M 52x2	107	201	98	60	33,3x2,4	250

Metrische wartel

Metrische wartel 24° conus zware serie 45°




GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch	F	H	L	K	S	O'Ring	bar
oa HPS-30MSOF20-90S-12	19	12	3/4"	M 30x2	67	129	29	36	16,3x2,4	420
HPS-36MSOF25-45S-12	19	12	3/4"	M 36x2	66	128	30	41	20,3x2,4	420
HPS-36MSOF25-45S-16	25	16	1"	M 36x2	81	154	33	41	22x2	414
HPS-42MSOF30-45S-16	25	16	1"	M 42x2	81	154	33	50	25,3x2,4	280
oa HPS-42MSOF30-90S-20	31	20	1 1/4"	M 42x2	99	187	39	50	25,3x2,4	250
HPS-52MSOF38-45S-20	31	20	1 1/4"	M 52x2	100	188	40	60	33,3x2,4	250
oa HPS-52MSOF38-45S-24	38	24	1 1/2"	M 52x2	116	210	44	60	33,3x2,4	250

Perskoppelingen HP serie

SAE 3000 PSI

SAE Flens 3000 PSI




oa

GSS Artikel nr	Slangmaat			Flens	Afmetingen (mm)					W.P. (max) bar
	DN	Size	Inch		H	L		A	O'Ring**	
HP-12SFH-3-12	19	12	3/4"	3/4"	52	113		38	24,99x3,53	350
HP-16SFH-3-12	19	12	3/4"	1"	58	119		44,5	32,92x3,53	350
HP-12SFH-3-16	25	16	1"	3/4"	53	125		38	24,99x3,53	350
HP-16SFH-3-16	25	16	1"	1"	59	131		44,5	32,92x3,53	350
HP-20SFH-3-16	25	16	1"	1 1/4"	63	135		51	37,69x3,53	250
HP-20SFH-3-20	31	20	1 1/4"	1 1/4"	64	151		51	37,69x3,53	250
HP-24SFH-3-20	31	20	1 1/4"	1 1/2"	69	156		60,5	47,22x3,53	200
HP-24SFH-3-24	38	24	1 1/2"	1 1/2"	69	163		60,5	47,22x3,53	200
HP-32SFH-3-24	38	24	1 1/2"	2"	74	168		71,5	56,74x3,53	200
HP-32SFH-3-32	51	32	2"	2"	76	173		71,5	56,74x3,53	200

SAE 3000 PSI

SAE Flens 3000 PSI 90°




oa

GSS Artikel nr	Slangmaat			Flens	Afmetingen (mm)					W.P. (max) bar
	DN	Size	Inch		H	L	K	A	O'Ring**	
HPS-12SFH90S-3-12	19	12	3/4"	3/4"	56	118	56	38	24,99x3,53	350
HPS-16SFH90S-3-12	19	12	3/4"	1"	56	118	61	44,5	32,92x3,53	350
HPS-12SFH90S-3-16	25	16	1"	3/4"	72	145	67	38	24,99x3,53	350
HPS-16SFH90S-3-16	25	16	1"	1"	72	145	68	44,5	32,92x3,53	350
HPS-20SFH90S-3-16	25	16	1"	1 1/4"	72	145	70	51	37,69x3,53	250
HPS-20SFH90S-3-20	31	20	1 1/4"	1 1/4"	91	178	85	51	37,69x3,53	250
HPS-24SFH90S-3-20	31	20	1 1/4"	1 1/2"	91	178	85	60,5	47,22x3,53	200
HPS-24SFH90S-3-24	38	24	1 1/2"	1 1/2"	108	202	100	60,5	47,22x3,53	200
HPS-32SFH90S-3-24	38	24	1 1/2"	2"	108	202	102	71,5	56,74x3,53	200
HPS-32SFH90S-3-32	51	32	2"	2"	143	281	129	71,5	56,74x3,53	200

SAE 3000 PSI

SAE Flens 3000 PSI 45°



oa


GSS Artikel nr	Slangmaat			Flens	Afmetingen (mm)					W.P. (max) bar
	DN	Size	Inch		H	L	K	A	O'Ring**	
HPS-12SFH45S-3-12	19	12	3/4"	3/4"	63	125	27	38	24,99x3,53	350
HPS-16SFH45S-3-12	19	12	3/4"	1"	67	129	31	44,5	32,92x3,53	350
HPS-12SFH45S-3-16	25	16	1"	3/4"	78	151	31	38	24,99x3,53	350
HPS-16SFH45S-3-16	25	16	1"	1"	79	152	32	44,5	32,92x3,53	350
HPS-20SFH45S-3-16	25	16	1"	1 1/4"	80	153	33	51	37,69x3,53	250
HPS-20SFH45S-3-20	31	20	1 1/4"	1 1/4"	99	187	39	51	37,69x3,53	250
HPS-24SFH45S-3-20	31	20	1 1/4"	1 1/2"	99	187	39	60,5	47,22x3,53	200
HPS-24SFH45S-3-24	38	24	1 1/2"	1 1/2"	117	211	46	60,5	47,22x3,53	200
HPS-32SFH45S-3-24	38	24	1 1/2"	2"	118	212	47	71,5	56,74x3,53	200
HPS-32SFH45S-3-32	51	32	2"	2"	152	250	58	71,5	56,74x3,53	200

** Koppelingen worden geleverd zonder o-ring !

Perskoppelingen HP serie

SAE 6000 PSI


SAE 6000 PSI



GSS Artikel nr	Slangmaat Ø interno tubo			Flens	Afmetingen (mm)					W.P. (max) bar
	DN	Size	Inch		H	L	A	O'Ring**		
HP-12SFH-6-12	19	12	3/4"	3/4"	58	120	41,3	24,99x3,53	420	
HP-16SFH-6-12	19	12	3/4"	1"	60	122	47,6	32,92x3,53	420	
HP-12SFH-6-16	25	16	1"	3/4"	59	132	41,3	24,99x3,53	415	
HP-16SFH-6-16	25	16	1"	1"	64	137	47,6	32,92x3,53	415	
HP-20SFH-6-16	25	16	1"	1 1/4"	68	141	54	37,69x3,53	415	
HP-20SFH-6-20	31	20	1 1/4"	1 1/4"	69	157	54	37,69x3,53	415	
HP-24SFH-6-20	31	20	1 1/4"	1 1/2"	79	166	63,5	47,22x3,53	415	
HP-24SFH-6-24	38	24	1 1/2"	1 1/2"	79	173	63,5	47,22x3,53	345	
HP-32SFH-6-32	51	32	2"	2"	97	195	79,4	56,74x3,53	345	

SAE 6000 PSI


SAE 6000 PSI 90°



GSS Artikel nr	Slangmaat			Flens	Afmetingen (mm)					W.P. (max) bar
	DN	Size	Inch		H	L	K	A	O'Ring**	
HPS-12SFH90S-6-12	19	12	3/4"	3/4"	56	118	61	41,3	24,99x3,53	420
HPS-16SFH90S-6-12	19	12	3/4"	1"	56	118	66	47,6	32,92x3,53	420
HPS-12SFH90S-6-16	25	16	1"	3/4"	72	145	67	41,3	24,99x3,53	415
HPS-16SFH90S-6-16	25	16	1"	1"	72	145	72	47,6	32,92x3,53	415
HPS-20SFH90S-6-16	25	16	1"	1 1/4"	72	145	79	54	37,69x3,53	415
HPS-20SFH90S-6-20	31	20	1 1/4"	1 1/4"	91	178	86	54	37,69x3,53	415
HPS-24SFH90S-6-20	31	20	1 1/4"	1 1/2"	91	178	93	63,5	47,22x3,53	415
HPS-24SFH90S-6-24	38	24	1 1/2"	1 1/2"	108	202	100	63,5	47,22x3,53	345
HPS-32SFH90S-6-32	51	32	2"	2"	143	240	131	79,4	56,74x3,53	345

SAE 6000 PSI

SAE 6000 PSI 45°




GSS Artikel nr	Slangmaat			Flens	Afmetingen (mm)					W.P. (max) bar
	DN	Size	Inch		H	L	K	A	O'Ring**	
HPS-12SFH45S-6-12	19	12	3/4"	3/4"	67	129	31	41,3	24,99x3,53	420
HPS-16SFH45S-6-12	19	12	3/4"	1"	71	132	34	47,6	32,92x3,53	420
HPS-12SFH45S-6-16	25	16	1"	3/4"	78	151	31	41,3	24,99x3,53	415
HPS-16SFH45S-6-16	25	16	1"	1"	82	155	35	47,6	32,92x3,53	415
HPS-20SFH45S-6-16	25	16	1"	1 1/4"	87	160	40	54	37,69x3,53	415
HPS-20SFH45S-6-20	31	20	1 1/4"	1 1/4"	100	188	40	54	37,69x3,53	415
HPS-24SFH45S-6-20	31	20	1 1/4"	1 1/2"	105	193	45	63,5	47,22x3,53	415
HPS-24SFH45S-6-24	38	24	1 1/2"	1 1/2"	117	211	46	63,5	47,22x3,53	345
HPS-32SFH45S-6-32	51	32	2"	2"	154	252	60	79,4	56,74x3,53	345

** Koppelingen worden geleverd zonder o-ring !

Perskoppelingen HP serie

SAE 9000 PSI


SAE 9000 PSI



GSS Artikel nr	Slangmaat			Flens	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch		H	L		A	O'Ring**	bar
HP-12SFH-9-12	19	12	3/4"	3/4"	64	126		41,3	24,99x3,53	420
HP-16SFH-9-12	19	12	3/4"	1"	65	127		47,6	32,92x3,53	420
HP-16SFH-9-16	25	16	1"	1"	69	142		47,6	32,92x3,53	415
HP-20SFH-9-16	25	16	1"	1 1/4"	72	145		54	37,69x3,53	415
HP-20SFH-9-20	31	20	1 1/4"	1 1/4"	73	161		54	37,69x3,53	415
HP-24SFH-9-20	31	20	1 1/4"	1 1/2"	80	168		63,5	47,22x3,53	415
HP-24SFH-9-24	38	24	1 1/2"	1 1/2"	81	175		63,5	47,22x3,53	345

SAE 9000 PSI


SAE 9000 PSI 90°



GSS Artikel nr	Slangmaat			Flens	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch		H	L	K	A	O'Ring**	bar
HP-12SFH90S-9-12	19	12	3/4"	3/4"	55	117	70	41,3	24,99x3,53	420
HP-16SFH90S-9-12	19	12	3/4"	1"	55	117	73	47,6	32,92x3,53	420
HP-16SFH90S-9-16	25	16	1"	1"	71	144	79	47,6	32,92x3,53	415
HP-20SFH90S-9-16	25	16	1"	1 1/4"	71	144	82	54	37,69x3,53	415
HP-20SFH90S-9-20	31	20	1 1/4"	1 1/4"	90	177	89	54	37,69x3,53	415
HP-24SFH90S-9-20	31	20	1 1/4"	1 1/2"	90	177	97	63,5	47,22x3,53	415
HP-24SFH90S-9-24	38	24	1 1/2"	1 1/2"	107	201	105	63,5	47,22x3,53	345

SAE 9000 PSI

SAE 9000 PSI 45°



GSS Artikel nr	Slangmaat			Flens	Afmetingen (mm)					W.P. (max)
	DN	Size	Inch		H	L	K	A	O'Ring**	bar
HP-12SFH45S-9-12	19	12	3/4"	3/4"	73	135	37	41,3	24,99x3,53	420
HP-16SFH45S-9-12	19	12	3/4"	1"	76	137	39	47,6	32,92x3,53	420
HP-16SFH45S-9-16	25	16	1"	1"	87	160	40	47,6	32,92x3,53	415
HP-20SFH45S-9-16	25	16	1"	1 1/4"	88	161	41	54	37,69x3,53	415
HP-20SFH45S-9-20	31	20	1 1/4"	1 1/4"	102	189	42	54	37,69x3,53	415
HP-24SFH45S-9-20	31	20	1 1/4"	1 1/2"	108	196	48	63,5	47,22x3,53	415
HP-24SFH45S-9-24	38	24	1 1/2"	1 1/2"	120	214	49	63,5	47,22x3,53	345

** Koppelingen worden geleverd zonder o-ring !