

AFDICHTINGSRINGEN (BONDED SEALS)



Materiaal staal verzinkt
Rubber NBR voering

Artikelnr.	binnen diameter	buitendiameter	dikte	barstdruk
PP45-A 1/8 SC	10,37	15,88	2,00	1050
PP45-B 1/4 SC	13,74	20,57	2,00	1080
PP45-C 3/8 SC	17,28	23,80	2,00	880
PP45-D 1/2 SC	21,54	28,58	2,50	800
PP45-E 5/8 SC	23,49	31,75	2,50	870
PP45-F 3/4 SC	27,05	34,93	2,50	740
PP45-G 7/8 SC	30,81	38,10	2,50	630
PP45-H 1 SC	33,89	42,80	2,50	560
PP45-J 1-1/4 SC	42,93	52,38	2,50	480
PP45-K 1-1/2 SC	48,44	58,60	3,25	480
PP45-M 2 SC	60,58	73,03	3,25	490
PP45-N 2-1/4 SC	66,68	79,50	3,25	460
PP45-P 2-1/2 SC	76,08	90,17	3,20	470
PP45 M4	4,50	7,00	1,00	870
PP45 M5	5,70	9,00	1,00	980
PP45 M6	6,70	11,00	1,00	1050
PP45 M8	8,70	14,00	1,00	1080
PP45 M10	10,70	16,00	1,50	1010
PP45 M12	12,70	18,00	1,50	870
PP45 M14	14,70	22,00	1,50	1050
PP45 M16	16,70	24,00	1,50	980
PP45 M18	18,70	26,00	1,50	890
PP45 M20	20,70	28,00	1,50	800
PP45 M22	22,70	30,00	2,00	770
PP45 M24	24,70	32,00	2,00	730
PP45 M26	26,70	35,00	2,00	730
PP45 M27	27,20	36,00	2,00	790
PP45 M33	33,70	42,00	2,00	630
PP45 M42	42,70	53,00	3,00	650
PP45 M48	48,70	59,00	3,00	560

RVS uitvoering standaard met VITON afdichting.